



SANTO

MASTER PROGRAM 2015

coated abrasives

RANGE	SANTO CODE	APPLICATION						Comments	BACKING	GRAIN	BONDING	GRIT AVAILABILITY
		Wood	Filler Plaster	Paint Varnish	PVC Composite	Metal						
Standard	B-12						Mostly used for surface hand sanding. Economical.	B	Flint	Glue / Glue	40 to 220	
	ABC-15						Surface and stock removal sanding and light sanding of fillers. Excellent cutting power and finish.	A, B or C	Alox	Glue / Glue	P 40 to 320	
	BC-17						Surface finishing, stock removal and plaster sanding	B or C	Sica	Glue / Glue	P 80 to 400	
	B-141						Waterproof paper for wet sanding of paint and lacquer surfaces	B, waterproof	Sica	Glue / Glue	P120 to 1200	
	C-55						Surface and stock removal with higher heat resistance due to resin bonding	C	Alox	Resin / Glue	P 40 to 240	
	D5-15						Extra strong backing. Durable. Surface and stock removal. Economical	E-modified	Alox	Glue / Glue	P36 to 320	
Superior	D-85						Extra strong bonding and increased lifetime.	D-superior	Alox	Resin / Resin	P 40 to 240	
	D5-54						Strong backing. Stock removal and surface sanding. Durable	E-modified	Alox	Resin / Glue	P 40 to 240	
	E-55						Excellent strength and heavy paper. Surface and stock removal sanding with superior surface finish. Extra durable. Also for power tool sanding. 'Liberty Green' quality.	E-superior	Alox	Resin / Glue	P 36 to 320	
Professional	BC-99L GOLD						Carbon and stainless steel, aluminium, hard wood, acrylic- and polyester. Anti clogging stearate coat and flexible latex backing.	B or C + Latex + Stearate	Alox	Resin / Resin	P 40 to 1000	
	D-99 GOLD						Non Latex version of BC-99L in D weight.	D + Stearate	Alox	Resin / Resin	P 40 to 1000	
	B-97L ZEBRA						Stain, sealer and lacquer. Anti clogging stearate coat and flexible backing.	B or C + Latex + Stearate	Sica	Resin / Resin	P 80 to 400	
	D-97L ZEBRA						Extra strong B-97L in D weight.	D + Latex + Stearate	Sica	Resin / Resin	P 80 to 400	
	D-621						Stained and lacquered surfaces. Special for high gloss up to grit 1500.	D	Alox	Phenol / Glue	P 360 to 1500	
	E-25						Cloggy woods (e.g. pine).	E-superior	Alox	Phenol / Glue	P 80 to 240	
	E-27						Resinous wood (pine, glue laminated, veneer).	E- superior	Sica	Phenol / Glue	P 36 to 120	
	F-37						Superior Resinous wood (pine, MDF laminated, veneer). Slate and Marble. Composite Materials. Long life. Extra strong.	F-superior	Sica	Phenol / Phenol	P 36 to 400	
	D 323 / 324						Heavy duty sanding wood, floor, removal paint and lacquer.	D, Fiber reinforced	Sica	Resin / Resin	P 12, 16, 24	
	Y-Pro						Heavy duty sanding wood, wet and dry steel / stainless steel.	Y-cloth < 150 < X-cloth	Alox	Phenol / Phenol	P 24 to 120	
	J-900-O						Soft wood, soft metal (brass, aluminium).	J-cloth Cotton	Alox	Phenol / Phenol	P 40 to 400	
	J-228						Hard wood, MDF, lacquer, dry grinding brass and non ferrous metals.	J-cloth Cotton	Sica	Phenol / Phenol	P 80 to 400	
	J-859						Hard wood, MDF, lacquer, metal. High temp resistance.	JJ-cloth Cotton + Filler coat	Alox	Phenol / Phenol	P 80 to 320	
X-925						Wood, carbon, stainless steel.	X-cloth	Alox	Phenol / Phenol	P 36 to 400		

Contact Santo for tailor made solutions and OEM

tel: +47 40 48 51 45

e-mail: santo@santo.no

www.santo-abrasives.com